Fresh
Fruit Vegetable

Frozen
Meat Seafood Ice Cream

Pharmaceutical
Medicine Drug

USB Connection

Built-in USB Connector
Directly plug into PC, No cable required

Integrated PDF generating
Software on-board, no software required

IP 67 Protected

IP67 Protection class
Food-safety and water-proof packaging

Qualified for Air Transport Monitoring
Complies to RTCA/DO-160G Environmental Conditions, qualified for air transport under active status.

GDP compliant

EN 12830 Compliant

Using Plustrace – G1

01 **Push START/STOP button to start**



02 **Put the started logger G1 to anywhere of your shipment**

03 **Connect to PC USB port**

04 **Directly get the pdf report automatically**

SPECIFICATION

Data logger type:	Single-Use data logger
Temperature range:	-30° C to +70° C (-22° F to 158° F)
Accuracy:	±0.5° C/0.9° F (-20° C/+40° C) otherwise ±1.0
Resolution:	0.1° C/° F
Storage capacity:	115200 Measurements
Life/Battery:	24 months/CR2032 button cell battery
Measurement interval:	5 minutes (standard - other options on request)
Recording time:	90 days (standard - other options on request)
Startup method:	Push start
Stop method:	Push stop or automatic stop when plug into PC.
Alarm type:	Single or cumulative - Up to 5 points
Protection class:	IPE67/NEMA 6
Dimensions:	76mm x 31mm x 4.5mm [L x W x H]
Weight:	approx 15g
Certified:	EN12830, CE, RoHS NIST
Calibration certificate:	Nvlap NIST traceable (United States)
Software:	Self -generated, no software required
Report:	Adobe PDF graphics
Automatic report:	PDF or CSV
PC connection:	USB2.0
Delivery contents:	Dispatch documents, certificate, sealeable pouch

PLUSTRACE Monitoring Solutions

Plustrace Technology Co.,Ltd
www.plustrace.com

Tel: +86 15617515536
Mail: info@plustrace.com